


CPC510 3U 5HP Compact PCI S.0 Intel Core i7 CPU Board with Conduction Cooling



Features

- Intel IvyBridge processor (2 cores, up to 1,7 GHz);
- Up to 4 GB soldered, dual-channel DDR3 SDRAM with ECC;
- 2x DisplayPort up to 2560×1600@60Hz at the front panel;
- 2x Gigabit Ethernet ports (front panel);
- 2x USB 2.0 (front panel);
- Intermodule communication (PICMG CPCI S.0 CompactPCI® Serial): two x8 FatPipe PCI-E; 3 x USB 2.0; 4x USB 3.0; 3 SATA II, 2 SATA III;
- Conduction cooling;
- Protective coating (optional);
- -40...+85°C;
- Windows 7 Embedded, Linux 2.6, QNX 6.5.

Technical Specification

Intel IvyBridge CPU (2/4 Cores)

- Intel i7 3517UE (DC, 2C/4T, 1,7 GHz, 1600 MHz, 4 MB, 17 W)

Panther Point PCH

Memory

- DDR3L SDRAM 1066, 1333 MHz with ECC up to 4 GB soldered, dual-channel.

Video Output (simultaneous output to 2 monitors)

- Two DisplayPort connectors (resolution up to 2560×1600@60Hz) at the front panel

PCI E Bus

- CPU Hosts. PCI E 2.0 support (up to 5GT/s):
 - Output via the PCI E switch to J1 and J2 CPCI Serial connectors with support for two x8 FatPipe#1 and FatPipe#2 devices;
 - Support for the Non Transparent mode for FatPipe#1;
 - Output via the PCI E switch to J4 CPCI Serial connector with support for four x4 devices.
- PCH Hosts. PCI E 2.0 support (up to 5GT/s):
 - Output to the mezzanine module on the left; support for 1 x4 or 4 x1 devices.

SMBUS Bus

- Compatibility with the 2.0 specification
- Speed up to 100 kbps

FLASH BIOS

- 64 Mbit SPI Flash

SATA II Interface

- Three ports are routed to the J3 CPCI Serial connector.

SATA III Interface

- Two interfaces are routed to the J3 CPCI Serial connector
- Support for RAID 0, 1, 5, 10

2 ports LAN 10/100/1000 Mbit at PCI E x4 Gen2

- Two interfaces are routed to the XS5 connector at the front panel
- Implementation of a server network adapter

USB ports

- Two USB2.0 ports are routed to connectors at the front panel
- 8/4 USB2.0 ports are routed to the J3 CPCI Serial connector*
- 4x USB3.0 ports are routed to the J3 CPCI Serial connector*

FRAM Memory

- 32 Kbyte, RAM 1 Kbyte for storing settings of the Bios Setup
- Implemented on the SPI Bus

Real time clock (RTC)

- Power is supplied from a CR 2032 lithium battery (3V)

Watch dog timer

- Internal with a possibility of programmed control

SGPIO Interface

- Support for signaling according to the SFF 8485 Specification

Hardware monitor

- Implemented via PECE/SMBUS interfaces
- Monitoring of three supply voltages
- Monitoring of the CPU temperature
- Monitoring of the PCB temperature
- Monitoring of the RAM temperature

Support for the power source management Indication

- Board Startup Diagnostics LED / Hot Swapping Light.SATA/SD Drives Access LED

- Two software controlled LEDs (user defined)
- Temperature state LED
- PCI Express Interconnections state LED

OS Programming Compatibility

- Windows 7 Embedded
- Linux 2.6
- QNX 6.5

Power Requirements

- Power voltage +12V, +5V_STBY (option)

Operating temperature range

- From -40°C to +85°C

Humidity

- Up to 80% non condensing

Vibration / Single shock resistance

- 5g/100g


MTBF

- More than 100,000 hours

* when USB 3.0 is used, four USB 2.0 ports are utilized by the USB 3.0 ports

CPC510 3U 5HP Compact PCI S.0 Intel Core i7 CPU Board with Conduction Cooling

Board Layout



Ordering Information

CPC510 Configuration

CPC510 - 01 - i72C1.7 - RAM4096 - RC - I

CPC510 Available Options

Coating	
\COATED	Protective Coating
Operating System Presetting	
\LNX	Linux 2.6
\Win7e	Windows 7 Embedded
\QNX	QNX 6.5

Other configurations and options are available upon request.

Delivery checklist

1. CPC510 module;
2. Package.

Corporate Offices

FASTWEL GROUP Co. Ltd
 108 Profsoyuznaya str.
 Moscow, Russia 117437
 Tel: +7 (495) 232-1681
 Fax: +7 (495) 232-1654
 E-mail: info@fastwel.com
 Web: www.fastwel.com

FASTWEL Corporation US
 Fastwel Corporation US
 6108 Avenida Encinas,
 Suite B, Carlsbad,
 CA 92011.
 Phone: 858-488-3663
 E-mail: info@fastwel.com



Ver. 1.12.2015

Product specifications are subject to change without notice

Fastwel