

IPC-SYS8FN (Advantix - powered by Fastwel) 1U High-Performance Fanless PC



Overview

The IPC-SYS8FN (Advantix – powered by Fastwel) is a high-performance fanless PC characterized by a low power consumption. The hallmark of this industrial fanless PC is the lack of noise from fans. Despite the compact size it has expansion slots and is suitable for installation in unmanned rooms.

Features

- CPU: Intel® Core™ i7-3610QE/Intel® Core™ i5-3610ME;
- Chipset: Intel® QM77;
- RAM: 2 – 16GB, 2 x DDR3-1333/1600, non ECC;
- Watchdog: programmable;
- Network: 2 x Ethernet 10/100/1000 controllers, each on PCI-E x1 bus;
- GPU: integrated Intel HD Graphics 4000, video memory up to 1GB, Dual Head support;
- Oper. temperature: +5~+40°C (AC ver.)/-40~+70°C (DC ver.);
- Power supply: 9-24V DC or 220V AC (2 options);
- OS compatibility: Microsoft XP Embedded, Windows 7, 8, 10, Linux;

Technical Specifications

CPU

- Intel® Core™ i7-3610QE (2.3GHz, 6MB, 4 x cores);
- Intel® Core™ i5-3610ME (2.7GHz, 3MB, 2 x cores);

Chipset

- Intel® QM77;

RAM

- 2 – 16GB, 2 x DDR3-1333/1600, non ECC, single-channel or two-channel;

Video subsystem

- Integrated GPU Intel HD Graphics 4000, video memory up to 1GB, support of Dual Head;

Expansion slots

- 2 x PCI full height, half length;
- 1 x Mini PCIe;

Bays

- 1 x 3.5" / 2.5" (internal);
- 2 x 5.25";

Disk subsystem

- 2 x bays for 2.5" HDD/SSD SATA Hot Swap or one 3.5" internal bay. Support of RAID 0/1;
- Connector for CF-SATA card for 64GB (without access from the outside);

Network

- 2 x Ethernet 10/100/1000 controllers, each on PCI-E x1 bus;

Audio

- 2-channel audio;

Ports

- 4 x USB 3.0 (rear panel), 2 x USB 2.0 (front panel);
- 1 x DVI-D, 1 x VGA, 1 x HDMI (with support of Dual Head);
- 2 x LAN (RJ-45);
- 1 x COM (it is possible to route up to 6 x COM-ports from the board: 3 x RS232 and 3 x RS232/422/485, routing 6 x COM-ports from the motherboard will occupy all free expansion slots);
- Audio In/Out;

Operating temperature range:

- from +5°C to +40°C, or from -20°C to +60°C (AC-version), or from -40°C to +70°C (DC-version);

Cooling

- Convection, passive;

Watchdog

- Programmable;

Power supply

- 9-24V DC or 220V AC (2 options);

Dimensions

- 380 (D) * 440 (W) * 44 (H);

Version design

- 1U;

Weight

- 7.5 kg;

Color


- Black;

OS compatibility

- Microsoft XP Embedded;
- Windows 7;
- Windows 8;
- Windows 10;
- Linux;

Warranty


- 2 years;



IPC-SYS8FN (Advantix - powered by Fastwel) 1U High-Performance Fanless PC


Layout

AdvantiX IPC-SYS8FN



Card cage

Rear view



Top view



Rear view (AC version)



Rear view (DC version)



IPC-SYS8FN (Advantix - powered by Fastwel) 1U High-Performance Fanless PC

Ordering information

IPC-SYS8FN (Advantix - powered by Fastwel) Configuration

IPC-SYS8FN \Options

Configurations

IPC-SYS8FN 1U High-Performance Fanless PC / Intel® Core™ i7-3610QE (2.3GHz, 6MB, 4 x cores) or Intel® Core™ i5-3610ME (2.7GHz, 3MB, 2 x cores) / RAM: 2 – 16GB, 2 x DDR3-1333/1600, non ECC, single-channel or two-channel / integrated Intel HD Graphics 4000, video memory up to 1GB, Dual Head support / 9-24V DC or 220V AC (2 options);

Delivery checklist

IPC-SYS8FN (Advantix - powered by Fastwel) delivery checklist contains:

1. IPC-SYS8FN (Advantix – powered by Fastwel) 1U High-Performance Fanless PC
2. Packaging.

Ver.1.08.2020

Product specifications are subject to change without notice

Corporate offices

FASTWEL GROUP Co., Ltd

108 Profsoyuznaya str.
Moscow, Russia 117437
Tel: +7 (495) 232-1681
Fax: +7 (495) 232-1654
E-mail: info@fastwel.com
Web: www.fastwel.com



Fastwel



Fastwel



Fastwel