



Features

- CPU: Freescale i.MX 6 Quad
- RAM: 1 GB
- Storage devices: CFast up to 64 GB; SDcard
- 15" display, 745 × 184 × 65 mm
- Resolution: 1024 × 768
- Brightness: 550 cd/m²
- EN50155 compliant

Overview

Rugged display module is used for displaying routing and promotional information in rail passenger cars. The module uses Ethernet network and requires no additional adapter units.

The device is designed for use in transport under conditions of adverse mechanical and electromagnetic effects in the wide range of environmental temperatures (EN50155).

General information

- · Displaying route information as schedule
- · Obtaining multimedia content from server
- · Displaying promotional and informational content

System

- CPU: Freescale i.MX 6 Quad
- RAM: 1 GB
- · Storage devices: CFast up to 64 GB, SDcard

Display

- Display size: 15"
- Resolution: 1024×768

- · Display colors: 16,7 M
- Parameters adjusted from the front panel: brightness, contrast etc.

Technical Specifications

Software support

• Preinstalled OS: Linux 2.6

Mechanical

- Protection: IP41
- Interfaces: 1×USB 2.0; 1×GbEthernet
- Dimensions: $745 \times 184 \times 65$ mm

Power

- Supply voltage: 43-160 V
- · Power consumption: no more than 40 W

Environmental

- Operating temperature range: from -40°C to +50°C
- Storage temperature range: from -45°C to +60°C
- Vibration resistance: 5–150 Hz /3g
- Shock resistance: 5 g

Ordering Information

IMS15 Configuration

IMS15 - 01

Versions 01

CPU: Freescale i.MX 6 Quad, RAM 1GB 15" rugged display, 1×GbEthernet, 1×USB, slot for CFast cards up to 64GB, slot for SDcards

IMS 15 - Network information module from Fastwel is fully configurable and can be customized according to the specific demands of your application.

Corporate Offices

FASTWEL GROUP Co. Ltd

108 Profsoyuznaya str. Moscow, Russia 117437 Tel: +7 (495) 232-1681 Fax: +7 (495) 232-1654 E-mail: info@fastwel.com Web: www.fastwel.com

FASTWEL Corporation US Fastwel Corporation US 6108 Avenida Encinas, Suite B, Carlsbad, CA 92011. Phone: 858-488-3663 E-mail: info@fastwel.com

Delivery checklist

IMS15 delivery checklist contains:

1. IMS15 - Network Information Module 2. Package

> Ver. 1.12.2015 Product specifications are subject to change without notice







ISO 9001:2008



- Aspect ratio: 4:3
- Brightness: 550 cd/m²
- Contrast ratio: 700:1
- · Visibility angles: 80 vertically, 70 horizontally

READY FOR