

# PPC-E15 (Advantix - powered by Fastwel)

## Intel® Core™ i5-4300U Fanless High-Performance 15" Panel PC



### Features

- CPU: Intel® Core™ i5-4300U / Intel® Core™ i7-4650U;
- Chipset: Intel® QM87 (sharing the same base with Haswell CPU);
- RAM: 2 – 16GB, 2 x DDR3L 1333/1600, non ECC, 2-channel;
- Protection: aluminum front panel, IP65;
- Screen: 15", resolution: 1024 x 768, with resistive touchscreen, luminance: 400 cd/m<sup>2</sup>, contrast ratio: 700:1;
- Network: 2 x Ethernet 10/100/1000 Intel® controllers WG1210AT and Intel® WG1218LM;
- Op. temperature: +5°C~+50°C (w/SSD), +5°C~+40°C (w/HDD);
- Power supply: 12-24V DC;
- OS compatibility: Microsoft Windows 7, Windows 8.1, Windows 10, Linux

### Overview

PPC-E15 (Advantix - powered by Fastwel) Intel® Core™ i5-4300U Fanless High-Performance 15" Panel PC is equipped with a 15" resistive touchscreen with resolution of 1024x768 and is characterized by a stylish industrial design and aluminum front panel with IP65 protection.

### Technical Specifications

#### CPU

- Intel® Core™ i5-4300U (1.9–2.9GHz, 3 MB cache, 2 x cores with HyperThreading support);
- Option: Intel® Core™ i7-4650U (1.7–3.3GHz, 4 Mb cache, 2 x cores);

#### Chipset

- Intel® QM87 (on a single base with Haswell CPU);

#### RAM

- 2 – 16GB, 2 x modules DDR3L 1333/1600, non ECC, 2-channel;

#### Screen

- 15", resolution: 1024 x 768, with resistive touchscreen, luminance: 400 cd/m<sup>2</sup>, contrast ratio: 700:1;

#### Expansion slots

- 1 x PCIe x1 full size, half-length, 2x Mini PCIe (1 x in coincidence with mSATA);

#### Disk subsystem

- 1 x bay for 2.5" HDD/SSD SATA, easy access from rear panel;
- 1 x external CFEX bay (closed with a cover), 1 x mSATA;

#### Network

- 2 x Ethernet 10/100/1000 Intel® controllers WG1210AT and Intel® WG1218LM;

#### Audio

- 2-channel, Realtek® HD Audio;

#### Ports

- 2 x USB 2.0, 2 x USB 3.0;
- 1 x HDMI, 1 x Display Port;
- 2 x LAN (RJ-45);
- 4 x COM (1 x RS-232/422/485, 3 x RS-232);

#### Watchdog

- programmable;

#### Power supply

- 12-24V DC;

#### Cooling

- Convection, passive;

#### Operating temperature range

- from +5°C to +50°C (with SSD), from +5°C to +40°C (with HDD);

#### Storage temperature

- from -20°C to +60°C;

#### Dimensions

- 118.9 (D) \* 425.4 (W) \* 330 (H);

#### Weight

- 8 kg, net weight;

#### Version design

- Aluminum housing, connector for VESA mount;

#### Protection

- IP65 for the front panel, IP20 for the rear panel;

#### OS compatibility

- Microsoft Windows 7;
- Windows 8.1;
- Windows 10;
- Linux;

#### Delivery checklist

- Phoenix female connector, wall mounting kit, power supply unit, power cable (with the models manufactured starting from 2018);

#### Warranty


- 2 years;




# PPC-E15 (Advantix - powered by Fastwel) Intel® Core™ i5-4300U Fanless High- Performance 15" Panel PC

## Layout


### PPC-E15 (Advantix – powered by Fastwel)



Bottom view



Top view



# PPC-E15 (Advantix - powered by Fastwel) Intel® Core™ i5-4300U Fanless High- Performance 15" Panel PC

## Ordering information

### PPC-E15 (Advantix - powered by Fastwel) Configuration

#### PPC-E15 \ Options

##### Configurations

##### PPC-E15

15" Fanless Panel PC / Core i5-4300U 1.9GHz / 8GB DDR3 / 120GB SSD / power supply unit / power cable;

#### Delivery checklist

##### PPC-E15 (Advantix - powered by Fastwel) delivery checklist contains:

1. PPC-E15 (Advantix – powered by Fastwel) Fanless 15" Panel PC
2. Phoenix female connector, wall mounting kit, power supply unit, power cable (with the models manufactured starting from 2018);
3. Packaging.

Ver.1.06.2020

Product specifications are subject to change without notice

## Corporate offices

#### FASTWEL GROUP Co., Ltd

108 Profsoyuznaya str.  
Moscow, Russia 117437  
Tel: +7 (495) 232-1681  
Fax: +7 (495) 232-1654  
E-mail: info@fastwel.com  
Web: www.fastwel.com



Fastwel



Fastwel



Fastwel